






Lechner

SOLUTIONS FOR PROFESSIONAL CONSTRUCTION



FIELDS OF APPLICATION

-  RESILIENT LINE
-  WOOD LINE
-  MARINE LINE
-  ARTIFICIAL GRASS LINE
-  EQUIPMENT AND ACCESSORIES LINE

PLANIPAST SPC/LVT

READY-TO-USE PASTE SKIMMING COMPOUND FOR LEVELLING AND FILLING FLOOR JOINTS

DESCRIPTION AND USES

PRODUCT FOR PROFESSIONAL USE ONLY

Ready-to-use paste product based on acrylic resins in water dispersion. Suitable for levelling and filling joints in stone, ceramic and stoneware floors without the use of primer. Its ease of application allows existing surfaces to be quickly prepared for floating and/or bonded installation of SPC, LVT, carpet flooring. Maximum permissible thickness: 2 mm per coat. It is also suitable for filling joints in walls and for grouting wood and plasterboard panels.

PRODUCT FEATURES



Application
Metal spatula



Suitable for indoor use



Suitable for heating substrates



Suitable for wheelchairs



Dry-to-walk-on time

60-90 min.

Drying time

2-3 hours



Storage

12 months in the original sealed packages



Chemical base

Synthetic resins in water dispersion and selected aggregates



Consumption

1.2 kg/m²/mm



Thickness per coat

up to 2 mm



Operating temperature

+10 - +30 °C



Cleaning

Water (as long as the product is fresh)

CERTIFICATIONS



Solvent-free product

METHOD OF USE

Floors to be levelled must be compact, undamaged, free of dust, clean and dry. PLANIPAST SPC/LVT has excellent adhesion on non-absorbent/smooth surfaces and therefore does not require prior treatment with primer. Pre-treat the surface with mechanical scratching, vacuum and apply the product in the desired thickness (maximum 2 mm per coat) with a metal trowel, even in several passes, until the necessary levelling is achieved to completely fill the joints, taking care to avoid exposing the product to the sun or strong air draughts during the drying phase. When completely dry, sand lightly and glue down LVT, SPC flooring with silane adhesives (POLIFLEX SPC/LVT), with two-component adhesives (GOMMAPUR), in the case of self-laying tiles, it is possible to use permanently tacky adhesives (HYCOSTIK).

Do not use solvent adhesives, acrylic adhesives in aqueous dispersion, in this case a cement skim coat with a minimum thickness of 2 mm should be used.

OTHER INFORMATION

It is not suitable for the direct laying of parquet. The drying times indicated in the specifications refer to a temperature of +20°C and a relative air humidity of 50%. Therefore, variations in temperature, ambient humidity and thickness may affect the drying times indicated.

INSTRUCTIONS

FOR SAFETY AND DISPOSAL: Consult the relevant safety data sheet before using the product. Gloves are recommended during use. Ventilate the room during and after use. Follow applicable safety regulations. Do not dispose of any residue into the ground, waterways or drains. For the disposal of the product and other waste deriving from the activity, scrupulously follow the provisions of Legislative Decree 152/2006 and subsequent modifications and integrations (Environmental Consolidation Act). For further information please contact our Technical Assistance Department. The content of this current sheet supplements and replaces the previous version, rendering it null and void.

WARNINGS: The data provided in this data sheet reflect our best theoretical and practical knowledge. However, since it is not possible for us to go into every detail, such information should not be considered as binding. In cases of doubt, please contact our technical offices.